



Rack and Pinion Jacks

Crank Handles



Siku

Safety Ratchet Crank (Raku)

- for use in cramped spaces
- lift by moving the ratchet upwards and downwards
- adjust the lifting or lowering movement by moving a lever
- the load is securely held at every height
- with collapsible handle
- without pawl

250 mm arm length:

- Square mounting 17 mm
- max. drive torque 60 Nm (braking torque)

300 mm arm length:

- Square mounting 17 mm
- max drive torque 120 Nm (braking torque)



Sifeku

Spring Loaded Safety Crank (Sifeku)

for special safe application

- without pawl
- silent
- recoil proof
- maintenance-free
- totally enclosed
- weather and temperature resistant
- braking effect at both ends
- at every height, the load is securely held in the pushing and pulling direction
- approved by the TÜV as an independent crank
- with collapsible handle

250 mm arm length:

- Square mounting 17 mm
- max. drive torque 60 Nm (braking torque)

Safety Crank (Siku)

- With one-sided braking effect
- The load is held securely at every height
- With collapsible handle
- Without pawl

250 mm arm length:

- Square mounting 17 mm
- max. drive torque 60 Nm (braking torque)

300 mm arm length:

- Square mounting 17 mm
- max drive torque 120 Nm (braking torque)



Raku