


MLF18 Accessories

Ultra High Vacuum Feedthrough & Accessories

AML produce a range of wiring accessories to complement their UHV compatible stepper motors. These components make installation of motors and other electrical items in vacuum much easier.



MLF18F

18-way feedthrough on a NW35CF (70mm OD) flange which mates with the MLF18VCF UHV connector, MLF18AC air-side connector or the MLF18NBL lead. It has individual glass compression seals with 1.5mm diameter gold-plated pins and is bakeable to 250°C. For non-motor applications observe the maximum ratings of 200V, 5A maximum per pin and 15A maximum per feedthrough.



MLF18AC

Air-side connector which mates with the MLF18F feedthrough. Bakeable to 250°C. Use this for manufacturing your own air-side leads.

**MLF18VCF**

18-way electrical female PEEK connector for use in UHV and is bakeable to 250°C. It mates with the MLF18F feedthrough and the MLF18VCM male connector. The gold plated, barbed crimp-contacts are attached to wires before insertion into the body and removed with a standard pin extraction tool if required. All AML motors are supplied with this type of crimp-contacts.

MLF18VCM

Male counterpart of the MLF18VCF.

**MLF18L**

3-meter, 250°C bakeable lead for use with AML stepper motor drives and up to 3 motors installed in one vacuum chamber. It mates with the MLF18F feedthrough.

**MLF18NBL**

3-meter non-bakeable lead for use with AML stepper motor drives and up to 3 motors installed in one vacuum chamber. It mates with the MLF18F feedthrough.

**PWB**

Set of 4, 250°C bakeable PEEK wiring bushes and M3 x 16mm vented screws. The four phase wires and thermocouple from a single motor are a light fit in the hole in the bush. Use one in situations where a 'P' clip would be used in air.

VTB6

6-way 250°C bakeable PEEK terminal block. Rating 2A per way, 200V and is compatible with all AML polyimide-covered wires. Supplied with M3 fixing screws, washers and nuts.

BC1.5

Pack of 10 barrel connectors 1.5mm bore.

**MLF18SKT**

Bag of 20 replacement crimp-contacts for use with MLF18VCF and MLF18AC.


MLF18PIN

Bag of 20 replacement crimp-contacts for use with MLF18VCM.

XCR24. Crimp tool for MLF18 crimp contacts.

XPX24. Pin extraction tool for MLF18 crimp contacts.

DIMENSIONS



ORDERING INFORMATION

Order Code	
MLF18F	Feedthrough, 18-way
MLF18VCF	In-vacuum female connector, 18-way
MLF18VCM	In-vacuum male connector, 18-way
MLF18AC	Air side connector, 18-way
MLF18L	SMD210 air side lead, 3m, bakeable
MLF18NBL	SMD210 air side lead, 3m non-bakeable
PWB	PEEK wiring bush x 4
VTB6	PEEK terminal block, 6-way
BC1.5	Barrel connectors. Pack of 10
MLF18SKT	Socket crimp, 24AWG. Bag of 20
MLF18PIN	Pin contact crimp, 20AWG. Bag of 20
XCR24	Crimp tool
XPX24	Pin extraction tool



Distributors for Australia & New Zealand
MOTION TECHNOLOGIES PTY LIMITED



24/22-30 Northumberland Road
Caringbah NSW 2229 Australia
Phone: (02) 9524 4782

sales@motiontech.com.au
www.motiontech.com.au

© 23/06/2023

AML pursues a policy of continuous improvement and reserves the right to make detail changes to specifications without consultation. E and OE.

www.arunmicro.com