


# JTG

## Bevel Gear Machine Screw Jack



<b>Descriptions</b>	<b>001</b>
<b>Materials</b>	<b>002</b>
<b>Selection Guide</b>	<b>003 - 007</b>
Selection Notes	003
Unit Converter	004
Sample Part Number	005
<b>Specifications</b>	<b>008</b>
<b>Screw Jack System Configurations</b>	<b>009</b>
<b>Overall Dimensions</b>	<b>010 - 012</b>
JTG15 - JTG19	010
JTG25 - JTG32	011
JTG40 - JTG45	012
<b>Other Products</b>	<b>013 - 016</b>
<b>Contact Us</b>	<b>017</b>

Contents





## Descriptions

**JTG Series Bevel Gear Machine Screw Jacks** are by the use of spiral bevel gears mechanism with self locking trapezoidal screws. These bevel gear jacks use bevel gears inside the housing instead of worm gearing. Bevel gears are more efficient than worm gearing—around 35% compared to 20%. So these bevel gear jacks offer higher efficiency and greater speed than other mechanical worm gear screw jacks, but a bit more expensive. As an added benefit, bevel gear jacks with three shafts also act as 90 degree bevel gearboxes, making them an ideal choice for multiple screw jack lift systems, which helps balance the difference in price. In the absence of vibration load, they are self-locking and precisely position loads, will hold loads without backdriving, and no need any brake mechanism or locking system. For low duty cycle applications, for hand-operated applications, or if back driving is not acceptable consider a bevel gear machine screw jack.

### Key Features

- Equipped with hardened spiral toothed bevel gear transmissions for high lifting speeds, greater duty cycles, high efficiency and long lifespan.
- Available in 6 sizes. Max. static load: 1 ton to 20 ton, Max. dynamic load: 300kg to 5 ton.
- Self locking trapezoidal screw offers maximum stroke of 6 m, precise positioning, and uniform speed.
- Basic designs: Translating screw, Keyed screw, and Rotating screw.
- Upright or Inverted mounting. Available in tension or compression loads.
- Standard with 1-start thread screw, custom 2-starts threads screw which offers increased travel speed and require a brake or external locking device to hold position.
- One, two and three drive shafts configurations are available.
- Power source: manual operation with hand wheel, electrically by motor driven.
- Can be applied either individually use or combined into a exactly synchronized lifting system(multiple jack systems), linked by connecting shafts, bevel gearboxes, couplings, electric motors, gear reducers, limit switches and pillow blocks etc.
- Optimal for low-speed operation: The driving system has less noise because machinery can be driven at a lower input speed.
- Simple and effective solution in comparison with hydraulic and pneumatic systems.
- Higher efficiency, higher lifting speed, higher duty cycle, longer lifespan.

## Materials

We use the best materials to guarantee the performance and lifetime of the screw jacks you purchased.

### Spiral Bevel Gears

- Lapped together in pairs, high quality alloy steel, case hardened.

### Lifting Screw

- C45 Steel as Standard. Custom Stainless Steel 304 or 316

### Input Shaft (Worm)

- Hardened, alloy steel. Custom Stainless Steel 304 or 316.

### Housing

- High-strength Casting Housing, Ductile Iron

### Travelling Nut / Safety Nut / Drive Sleeve

- High strength bronze ZQA19-4 (Casting aluminum bronze) as Standard.  
Custom bronze ZCuSn10Pb1(Casting tin bronze).

### Bearing

- Anti-friction Tapered Roller Bearings. Custom Stainless Steel 304.





**Selection Guide**

**Selection Notes**

- (01) Bevel Gear Screw Jacks and Lifting Systems are for industrial use only, not recommended for transporting personnel.
  - (02) Carefully consider bevel gear jack ratings before making a selection. Be sure that the dynamic or static load carried or sustained by jack does not exceed its maximum capacity.
  - (03) Carefully consider the combination of screw shaft speed (rpm) and rated load. Also, take extra care in verifying rated buckling load and screw shaft speed (rpm). Exceeding the data provided in this catalog can cause major damage to the system.
  - (04) Make sure that the surface temperature of the housing does not exceed temperature of -15°C to +80°C during operation. If using a traveling nut jack, measure the traveling nut surface temperature. Make sure all the rotating parts are completely stopped before proceeding to measure.
  - (05) The maximum input speed is 1500 rpm as long as the input power does not exceed the jack's maximum allowable input power.
  - (06) Bevel Gear Jack can not be operated continuously. Duty cycle based on 30 minutes.
    - **Note:** Below duty cycles are based on ambient temperatures 20°C. For ambient temperatures higher than 20 °C, the duty cycle (ED) must be reduced.
      - \* Screw Jack with Trapezoidal Screw (Bevel Gear Machine Screw Jack) duty cycle ≤ 35%ED.
      - \* Screw Jack with Ball Screw (Bevel Gear Ball Screw Jack) duty cycle ≤ 60%ED.
    - **Note:** For operation longer than that mentioned above or for any continuous operation, the jacks temperature must be monitored and should not exceed 80°C maximum in order to determine its duty cycle.
- Duty Cycle (%ED) = [1 Duty Cycle / (1 Duty Cycle + 1 Rest Cycle)] x 100%**
- (07) Be sure not to exceed the maximum input torque for multiple screw jack systems by verifying the rated input torque for each jack.
  - (08) Be sure that starting torque is 200% or more of required running torque.
  - (09) Be sure that ample driving power is available to drive the jack when using in temperatures below 0°C. Low temperatures decrease the jack's efficiency due to the increased grease viscosity inside the jack's gearbox.

**Selection Guide**

- (10) Although Screw Jack with **Single-start** Trapezoidal Screw (Bevel Gear Machine Screw Jack) has self-locking feature, vibration and shock may affect its efficiency, in which case a brake motor or extra braking device is required. Screw Jack with **Double-start** Trapezoidal Screw (Bevel Gear Machine Screw Jack) is considered not self-locking will require a brake or other holding device. Screw Jack with Ball Screw (Bevel Gear Ball Screw Jack) can backdrive because of their extremely high efficiencies and require some means of holding the load, such as a brake motor.
- (11) When jacks are working, can not force to stop, may result in the jacks damage or injury personnel.
- (12) When Bevel Gear Ball Screw Jack are under loads, can not change the motor drive to manual operation. Because the loads will cause the input shaft to rotate very dangerously.
- (13) Mechanical stops (Stop Nuts) are not provided on the lifting screw unless requested. Therefore, it is possible to drive the screw out of the jack's housing
- (14) Never approach or touch the rotary parts (input shaft, etc.) or the lifting screw during operation.
- (15) Bellows Boots and Protective Tubes should be used to protect and keep the lifting screw clean in dusty or abrasive environments.

**Unit Converter**

- 1 ft = 304.8 mm
- 1 in = 25.4 mm
- 1 m = 10 dm = 100 cm = 1000 mm
- 1 in-lb = 0.113 Nm
- 1 Nm = 0.737 ft-lb
- 1 ft-lb = 1.356 Nm
- 1 lb = 0.454 kg
- 1 kg = 2.205 lb = 1000 g
- 1 N = 0.1 kg
- 1 t = 1000 kg = 10 kN = 2000 lb
- 1 m/min = 1000 mm/min = 16.7 mm/sec
- 1 in/sec = 25.4 mm/sec
- 1 ft/sec = 304.8 mm/sec
- 1 hp = 0.75 kW
- °C = (°F-32) / 1.8
- °F = °C x 1.8 + 32



**Selection Guide**


**Sample Part Number ( Example ):**

**JTG25 - US - 300 - 2 - II - 2SR - CU - PP**  
 (1) (2) (3) (4) (5) (6) (7) (8)

**(1) Models & (4) Gear Ratios**

JTG15 ( Tr24x4 ) 2.5 : 1 ratio	JTG19 ( Tr32x6 ) 2.5 : 1 ratio	JTG25 ( Tr40x7 ) 3 : 1 ratio
JTG32 ( Tr50x10 ) 3 : 1 ratio	JTG40 ( Tr65x12 ) 3 : 1 ratio	JTG45 ( Tr80x12 ) 3 : 1 ratio

**(2) Basic Designs and Configurations**



**2.1) "US" and "IS" are Bevel Gear Machine Screw Jacks.** A translating jack has a lifting screw that moves through the gearbox. A nut is integrated with the bevel gear such that the bevel gear and nut rotate together. When the lifting screw is held to prevent rotation through the use of guides (guided load) or by attaching a common load across multiple jacks, the lifting screw will move linearly through the gearbox to move the load. Most applications use this jack design


**2.2) "UK" and "IK" are Anti-rotation Bevel Gear Machine Screw Jacks.** An anti-rotation jack is attached Square Guide Tube for non-rotation. A square guide tube is attached to either the top or bottom of the Screw Jack. A square nut is attached to the end of the Lifting Screw which is then fitted inside the tube, preventing rotation. The Square Guide Tube is supplied with lube fittings. It is ideal for use in applications where a single jack must extend to meet and move a load to which it is not attached (unguided). The anti-rotating jacks are mostly used on larger jacks and where the lifting force is high in relationship to the nominal capacity or where the travel is long.

• **Note:** Input torque required will increase by approximately 8%.

**2.3) "UR" and "IR" are Bevel Gear Machine Screw Jacks.** A rotating jack has a lifting screw that moves a nut as it turns. It is important to restrain the rotation of the traveling nut by Applying a significant load, or more commonly by guiding the load or attaching the load across multiple jacks. The lifting screw is fixed to the bevel gear. This causes the load, which is attached to the travel nut, to move along the lifting screw. The Rotating Jacks mount flush and they are ideal for applications where the physical space does not allow the lifting screw to extend below or above the housing.


**Selection Guide**

**(3) Stroke and (5) Screw End Fittings**




- Stroke is travel expressed in millimeter(mm) or inches and not the actual screw length.
- Standard Lifting Screw End Fittings: Top Plate (I), Clevis End (II), Plain End (III), Threaded End (IV), Forked End (VI) and Rod End (VII). Custom End Fittings are acceptable.

**(6) Input Shafts Codes and Motor Flange Adapters Codes (Top View)**



**(7) Gears Mounting Postions**





**Selection Guide**

**Sample Part Number**

**(7) Accessories**



**Specifications**

**Remarks:**

- 1) Overall efficiency is under grease lubrication.
- 2) Self-locking under single lead screw and static conditions.
- 3) They maximum dynamic load is under Euler II(fully guided).

Model	JTG15	JTG19	JTG25	JTG32	JTG40	JTG45
Maximum static load capacity (kgf)	1000	3000	5000	10000	15000	20000
Maximum dynamic load capacity (kgf)	300	1000	1500	2500	3500	5000
Trapezoidal screw sizes (mm)	Tr24 x 4	Tr32 x 6	Tr40 x 7	Tr50 x 10	Tr65 x 12	Tr80 x 12
Gear ratio	2.5:1	2.5:1	3:1	3:1	3:1	3:1
One Turn of Input Shaft, Travel (mm)	1.6	2.4	2.33	3.33	4	4
Overall Efficiency %	30%					
Travel Nut Material	Aluminum Bronze					
Housing material	Ductile Iron					



**Screw Jack System Configurations**

**Two Jacks**



**Four Jacks**



**Six Jacks**



**Eight Jacks**




**Fourteen Jacks**




**Overall Dimensions**


**JTG15**




Upright




Inverted



Plan View




Upright




Inverted

**Screw End Types and Dimensions**




I Top Plate

II Clevis End




III Plain End




IV Thread End


**JTG19**




Upright




Inverted



Plan View




Upright




Inverted

**Screw End Types and Dimensions**




I Top Plate

II Clevis End



III Plain End




IV Thread End

\*. Dimensions are subject to change without notice




Overall Dimensions


JTG25




Upright




Inverted



Plan View




Upright



Inverted

Screw End Types and Dimensions




I Top Plate

II Clevis End


III Plain End

IV Thread End


JTG32




Upright




Inverted



Plan View




Upright



Inverted

Screw End Types and Dimensions



I Top Plate

II Clevis End


III Plain End

IV Thread End


\*. Dimensions are subject to change without notice

Overall Dimensions


JTG40




Upright




Inverted



Plan View




Upright



Inverted

Screw End Types and Dimensions




I Top Plate

II Clevis End


III Plain End

IV Thread End


JTG45




Upright




Inverted



Plan View




Upright



Inverted

Screw End Types and Dimensions



I Top Plate

II Clevis End

III Plain End

IV Thread End

\*. Dimensions are subject to change without notice



**Other Products**

**Cubic Machine Screw Jack**

- Cubic design permits any mounting position.
- High static loads, best for slow movement and low duty cycles.
- Static load capacities from 2.5 kN to 500 kN as Standard.
- Translating, Anti-rotation (keyed) and Rotating Screw configurations.
- Self locking trapezoidal screw offers maximum stroke of 7500 mm.
- Power source: Manual operation, Motor drive.
- Single jack, or synchronization of multiple jacks arrangement



**Cubic Ball Screw Jack**

- Cubic design permits any mounting position.
- High duty cycle, high precision, high speed, less power and long service life.
- Static load capacities from 10 kN to 350 kN as Standard.
- Translating, Anti-rotation and Rotating Screw configurations.
- Not self-locking ball screw offers maximum stroke of 6000 mm.
- Power source: Brake motor drive. Not suited for manual operation.
- Single jack, or synchronization of multiple jacks arrangements.



**Classic Machine Screw Jack**

- Classic design, no need to attach any construction elements to the housing.
- High static loads, best for slow movement and low duty cycles.
- Static load capacities from 0.5 ton to 100 tons as Standard.
- Translating, Anti-rotation (keyed) and Rotating Screw configurations.
- Self locking trapezoidal screw offers maximum stroke of 7500 mm.
- Power source: Manual operation, Motor drive.
- Single jack, or synchronization of multiple jacks arrangements.



**Stainless Steel Screw Jack**

- Classic design, no need to attach any construction elements to
- Complete Stainless Steel Screw Jack design.
- High static loads, best for slow movement and low duty cycles.
- Static load capacities from 1 ton to 20 tons as Standard.
- Translating, Anti-rotation (keyed) and Rotating Screw configurations.
- Self locking Stainless Steel trapezoidal screw offers maximum stroke of 7500 mm.
- Power source: Manual operation, Motor drive.
- Single jack, or synchronization of multiple jacks arrangements.



**Other Products**

**Classic Ball Screw Jack**

- Classic design, no need to attach any construction elements to the housing.
- High duty cycle, high precision, high speed, less power and long service life.
- Static load capacities from 1 ton to 35 tons as Standard.
- Translating, Anti-rotation and Rotating Screw configurations.
- Not self-locking ball screw offers maximum stroke of 6000 mm.
- Power source: Brake motor drive. Not suited for manual operation
- Single jack, or synchronization of multiple jacks arrangements.



**Bevel Gear Machine Screw Jack**

- High efficiency, high lifting speed, high duty cycle, long lifespan.
- Spiral bevel gear mechanism are used, with 2:1, 2.5:1 and 3:1 ratios.
- Static load capacities from 400 Kg to 3500 Kg as Standard.
- Translating, Anti-rotation (keyed) and Rotating Screw configurations.
- Self locking trapezoidal screw offers maximum stroke of 6000 mm.
- Power source: Manual operation, Motor drive.
- Single jack, or synchronization of multiple jacks arrangement



**Bevel Gear Ball Screw Jack**

- Higher efficiency, higher lifting speed, higher duty cycle, longer lifespan.
- Spiral bevel gear mechanism are used, with 2:1, 2.5:1 and 3:1 ratios.
- Static load capacities from 400 Kg to 3500 Kg as Standard.
- Translating, Anti-rotation and Rotating Screw configurations.
- Not self-locking ball screw offers maximum stroke of 6000 mm.
- Power source: Brake motor drive. Not suited for manual operation.
- Single jack, or synchronization of multiple jacks arrangements.



**Screw Jack Lifting Systems**

- Lifting systems are not limited to the number of screw jacks. Commonly used are 2, 4, 6, 8 jack systems.
- Full synchronization, self-locking, precision positioning, easy installation and operation, maintenance free.
- From a few kilograms to heavy-duty several hundred tons.
- Complete lifting systems with geared motors, shafting and couplings available.
- Power source: Synchronized drive from a single electric motor.
- With Inverter driven motor, soft start and stop, variable lifting speeds are all available.





**Other Products**

**Cubic Bevel Gearbox**

- Modular design spiral bevel gearboxes with cubic housing.
- Ultra Compact Design. All-round tapped holes for universal mounting, 6 possible mounting positions.
- Gear ratios of 1:1, 2:1, 3:1, 4:1 and 5:1 are actual ones.
- Power Ratings up to 156 kW. Torque Ratings up to 1199 N.m.
- Gear transmission average efficiency up to 94%.
- 2-way, 3-way and 4-way Configurations.
- Solid Shaft, Hollow Shaft, and Direct motor mount or via motor flanges.
- High efficiency, high transmission capacity, low backlash, Noiseless operation, low running temperature and long service life.



**Classic Bevel Gearbox**

- Used in pairs case hardened alloy steel spiral bevel gears.
- Gear ratios of 1:1, 1.5:1, 2:1, 2.5:1, 3:1, 4:1 and 5:1 are actual ones.
- Power Ratings up to 335 kW. Torque Ratings up to 5713 N.m.
- Gear transmission average efficiency up to 94%.
- 2-way, 3-way and 4-way Configurations.
- Solid Shaft, Hollow Shaft, and Direct motor mount or via motor flanges.
- Various Shafts Arrangements, Rotation Directions and Mounting Positions available.
- High efficiency, high transmission capacity, low backlash, noiseless operation, low running temperature and long service life.



**Lightweight Bevel Gearbox ( Aluminium Alloy)**

- Quality finished casing by die-casting, in lightweight aluminium alloy.
- Compact design, small-sized, ultra-lightweight, universal mounting.
- Utilizing carburized case-hardened spiral bevel gears
- Gear ratios of 1:1 and 2:1 are actual ones.
- Power Ratings up to 4.94 kW. Torque Ratings up to 40 N.m.
- Gear transmission average efficiency up to 94%
- 2-way and 3-way Configurations.
- High efficiency, low backlash, quiet operation, maintenance free, low running temperature and long service life.



**Other Products**

**Electric Cylinders**

- Be basically screw jacks with travelling nut, but with lifting cylinder design.
- High static loads, best for slow movement and low duty cycles.
- Static load capacities from 2.5 ton to 10 tons as Standard.
- Self-locking, precise positioning, and uniform speed.
- Power source: Manual operation, Motor drive.
- Single unit, or synchronization of multiple units.
- A better choice over hydraulic actuators or pneumatic cylinders with this clean alternative, simpler to install, control, low maintenance and a quieter solution.



**Electric Linear Actuators**

- Parallel or In-Line drive configurations.
- Self-locking ACME screw and nut, driven by an electric motor, through a reduction gearbox.
- Low maintenance due to high-quality grease and enclosed design.
- Load capacities from 100 Kgf to 15 tons as Standard (Parallel)
- Load capacities from 10 Kgf to 1000 Kgf as Standard (In-Line).
- Low noise system, higher dynamic capacity, higher speed capability and longer life.
- Low power consumption and running costs, no oil leaks, contamination or fire risk.
- Easy installation with two trunnion mounting feet, no pipework, powerpack and valves.
- Be a real alternative to pneumatic and hydraulic cylinders.



**Customized and molded products**

